

PERFWIPE ESD Trays Specification

Descriptions:

ESD Plastic Trays is manufactured from conductive plastic material PP , Specifically designed for component assembly and for compatibility with conveyors or cart transport systems. These ESD Plastic Trays of ESD conveyor trays and ESD assembly trays are specifically designed for electrical component assembly and compatibility with conveyors or cart transport systems, and possess superior physical properties over thermoplastic and corrugated products.

ESD Plastic Trays of conveyor and assembly trays ensure complete protection from electrostatic discharge for the life of the product.

They may be used consistently in temperatures ranging from -60° to 250° F (-51° to 121° C) and are resistant to cutting oils, greases, solvents, mild acids and alkaline solutions within a pH rating of 3.0 - 10.0.

ESD Plastic Trays is easily cleaned in hot water or steam with standard detergents.

Features:

Specifically designed for component assembly and for compatibility with conveyors or cart transport systems

Meets or exceeds ANSI/ESD standards for ESD protection

ESD Plastic Trays had Operating temps of -60° to 250° F (-51° to 121° C)

Surface resistance: 10^6 - 10^{10} ohm/cm

Inherent fiberglass strength and durability

Application:

ESD trays provide effective protection for handling PC boards and electronic components in assembly, packaging, storage and processing areas.

Ideal for storage, transport and handling of electronic components

Order Informations:

Code	External size (mm)	Internal size (mm)
SSC3022	450x300x60	430x280x50
SSC3022A	320x235x43	310x225x35
SSC3022B	375x250x65	345x250x60
SSC3022C	440x295x80	410x265x75
SSC3022D	560x375x75	525x340x70
SSC3022E	440x290x50	400x265x45
SSC3022F	226x160x29	213x153x25
SSC3022G	280x190x26	272x182x24
SSC3022H	309x283x30	136x58x20 / Square-Lattic 10
SSC3022L	480x328x42	445x292x35
SSC3022M	615x420x95	570x370x90
SSC3022N	450x300x45	430x280x38
SSC3021	375x310x30	355x295x22
SSC3022J	375x310x20	355x295x15
SSC3022K	360x360x85	350x350x75
SSC3022O	375x275x40	360x260x35
SSC3022P	530x365x43	510x350x33
SSC3022Q	450x300x35	215x140x28 / Square-Lattic 4
SSC3022S	345x260x35	302x212x34
SSC3022T	220x175x26	185x140x23
SSC3022U	285x224x30	240x182x28
SSC3022R	654x454x29	620x413x26 TR>121° C