

SPECIFICATION



Current Rating: 3 AMP
 Insulation Resistance: 1000MΩ Min.
 Contact Resistance: 20mΩ Max.
 Dielectric Voltage: 500V AC for one minute
 Operation Temperature: -40 °C to +105 °C

MATERIAL




Insulator: Hi-Temp. Thermoplastic, UL94V-0, Black
 Contact Pin: Copper Alloy

ORDER INFORMATION

5 P H 1 R D A 2 5 - 2 X X X X N N X U - A B C - 0 0



Recommended PCB Layout
 (PCB TOLERANCE ±0.1)



Old Part No. :PH1RD25-2XX-U

△	Modify order information	B	2017/01/25 Gary
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE

糧德精密有限公司
 Amtek Technology Co., Ltd.
 TEL: 886-2-2260-6878
 FAX: 886-2-2260-8030

品名 TITLE	PIN HEADER 2.54mm D/R R/A DIP TYPE				頁數 Page	1/1
品號 PART NO.	5PH1RDA25-2XXXXNXXU -XXXXXXXXXX-00			繪圖 DRAWN	Mia	2015/08/20
圖號 DRAWING NO.	GN016-GA144	版本 REV.	B	核對 CHECKED	John	2015/08/20
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	John	2015/08/20
公差 TOLERANCE	.X ± 0.35 .XX ± 0.25	.X° ± 3	單位 UNIT	mm	THIRD ANGLE PROJECTION	