

PRODUCT DATA APPROVAL SHEET

Core- EE<u>5521</u>

Cosmo Ferrites Ltd. - INDIA

Appearance & Shape: To be free from any defect such as flow, burrs, unevenness etc, As per IEC standards. **Effective Parameters irrespective of material grade (per set)**

Effective Length (L_e): 120.0mm
Effective Area (A_e): 354.0mm²
Effective Area (A_{Min}): 351.0mm²
Effective Volume (V_e): 42500mm³

Approximate Weight (without Gap): 218g/Set



EE5521 Un-gapped

Test Conditions: 1KHz/150mV/CFR COIL,N=100/25°C

| Material Grade | Initial Permeability (μ _{iac}) | AL Value (nH) | P _v (W/set) | Ordering code |
|-------------------|--|----------------|-----------------------------|---------------|
| CF297 | 2300 ± 20% | 6700 +30%/-20% | <3.83 (100mT,100kHz, 100°C) | CF297 EE5521 |

Dimensions:

| Dimension | Nominal (in mm) | Maximum (in mm) | Minimum (in mm) |
|-----------|--------------------|--------------------|--------------------|
| Α | 55.0 | 56.2 | 54.1 |
| В | 37.5 | 38.7 | 37.5 |
| С | 27.8 | 27.8 | 27.2 |
| D | 18.5 | 19.3 | 18.5 |
| E | 17.2 | 17.2 | 16.7 |
| F | 21.0 | 21.0 | 20.4 |

C B D D F

For Cosmo Ferrites Limited-INDIA

Checked By: J.C. Approved By: B.S. Authorized By: KSR

Date: 08-05-2024 (ISSUE NO. 1)

Customer's Approval Authorized Signatory:

Name: Date:

NOTE: <u>Please send this Data Sheet back to Cosmo Ferrites Ltd. after approval. If not received back within 15 days, it will be presumed that all the specifications given in the consent/data sheet are acceptable to the concerned.</u>