



P.C.B LAYOUT  
(REFERANCE PCB T=1.20~1.60mm)

■ Specifications :

- Voltage rating: 250V AC / DC
- Current rating: 3A AC / DC
- Withstanding voltage: 1000V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance: ≥1000MΩ
- Contact resistance: ≤20mΩ
- After environmental testing: ≤40mΩ
- Material(Pin): Brass

Circuits	Dimensions(mm)			Circuits	Dimensions(mm)		
	A	B	C		A	B	C
2x5P	8.00	12.00	7.30	2x13P	24.00	28.00	9.20
2x6P	10.00	14.00	9.20	2x14P	26.00	30.00	9.20
2x7P	12.00	16.00	9.20	2x15P	28.00	32.00	9.20
2x8P	14.00	18.00	9.20	2x16P	30.00	34.00	9.20
2x9P	16.00	20.00	9.20	2x17P	32.00	36.00	9.20
2x10P	18.00	22.00	9.20	2x18P	34.00	38.00	9.20
2x11P	20.00	24.00	9.20	2x19P	36.00	40.00	9.20
2x12P	22.00	26.00	9.20	2x20P	38.00	42.00	9.20

								一般公差 GENERAL TOLERANCE	NINGBO KLS ELECTRONIC CO; LTD				料号 PART NO. L-KLS1-XL12-2.00-2xXX-R			
								.X ±0.30					核准 APPROVAL			
								.XX ±0.20	审核 CHECK							
								.XXX ±0.10					绘图 DRAWN			
日期 DATE	旧版次 OLD REV	新版次 NEW REV	变更编号 ECN	变更内容 DESCRIPTION	审核 CHECK	核准 APPROVAL	角法 PROJECT	角法 PROJECT	日期 DATE							
													2018/07/11			
									Li Hao							
													Zhang Bowen			
									Wang Lianxi							
													2018/07/11			
									MM							
													1:1			
									A							