

ORDER INFORMATION



SPECIFICATIONS

Current Rating: 2 AMP
 Insulation Resistance: 1000MΩ Min.
 Contact Resistance: 20mΩ Max.
 Dielectric Voltage :500V AC for one minute
 Operation Temperature: -40°C to + 105°C


MATERIAL

Insulator: Hi-Temp. Thermoplastic, UL94V-0, Black
 Contact Pin: Copper Alloy

5 P H 2 D D A 2 0 - 1 X X X X N N X U - A L 1 B - 0 0



Recommended PCB Layout
 (PCB TOLERANCE ±0.1)



Old Part No. : PH2D20-1XX-U

△	ECN No.:180310,Remove the Cap & Revise the Package option .	Roy	2018/03/22
△	ECN No.:171201, Revise the Cap.	Roy	2017/12/01
△	Modify order information	Gary	2017/02/02
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE

耀德精密有限公司
 Amtek Technology Co., Ltd.
 TEL: 886-2-2260-6878
 FAX: 886-2-2260-8030

品名 TITLE	PIN HEADER 2.0mm S/R V/T DIP TYPE				頁數 Page	1/1
品號 PART NO.	5PH2DDA20-1XXXXNXXU -XXXXXXXXXX-00			繪圖 DRAWN	Athena 2015/08/14	
圖號 DRAWING NO.	GN016-GA216	版本 REV.	D	核對 CHECKED	Josh 2018/03/22	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2018/03/22	
公差 TOLERANCE	.X ±0.38 .XX ±0.25	單位 UNIT	mm	THIRD ANGLE PROJECTION		