PRODUCT-DETAILS

T4V-HA 250 TMA 200-2000 3p F F 800V AC

T4V-HA 250 TMA 200-2000 3p F F 800V AC



General Information

Extended Product Type:	T4V-HA 250 TMA 200-2000 3p F F 800V AC
Product ID:	1SDA083662R1
EAN:	8015644905040
Catalog Description:	T4V-HA 250 TMA 200-2000 3p F F 800V AC
Long Description:	C.BREAKER TMAX T4V-HA 250 800V AC FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMD R 200-2000 A IEC/CCC
Display Name:	T4V-HA 250 TMA 200-2000 3p F F 800V AC

ABB EcoSolutions

Environmental Product Declaration - EPD:	No declaration needed

Material Compliance

REACH Declaration:	9AKK108466A1425
RoHS Declaration:	9AKK108466A1424

© 2026 ABB. All rights reserved.

RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT):	9AKK108467A5658
Toxic Substances Control Act - TSCA:	9AKK108467A8326

Environmental

Environmental Information:	9AKK10103A1057 9AKK108467A6707

Ordering

Order Code US and Canada:	T4P8VE200TW
EAN:	8015644905040
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85352100

Dimensions

Product Net Width:	140 mm
Product Net Height:	205 mm
Product Net Depth / Length:	103.5 mm
Product Net Weight:	2.5 kg

Container Information

Package Level 1 Units:	box 1 piece
Package Level 1 Width:	248 mm
Package Level 1 Height:	240 mm
Package Level 1 Depth / Length:	285 mm
Package Level 1 Gross Weight:	2.5 kg
Package Level 1 EAN:	8015644905040

Additional Information

Circuit Breaker Type to be Associated:	Power Distribution
Product Main Type:	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker
Version:	F

© 2026 ABB. All rights reserved.

Technical

Current Type:	AC
Electrical Durability:	Ue = 800 V 2000 cycle
Mechanical Durability:	20000 cycle
Number of Poles:	3P
Rated Current (I_n):	200 A
Rated Frequency (f):	50/60 Hz
Rated Impulse Withstand Voltage (U_{imp}):	8 kV
Rated Insulation Voltage (U_i):	1000 V
Rated Operational Voltage:	800 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(800 V AC) 12 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(800 V AC) 25 kA
Rated Uninterrupted Current (I_u):	200 A
Rated Voltage (U_r):	800 V AC
Release:	TMA
Release Type:	TM
Remarks:	ATLAS
Short-Circuit Performance Level:	V
Standards:	IEC
Sub-type:	T4
Suitable for IT Networks:	Yes, 800V

Certificates and Declarations

Data Sheet, Technical Information:	1SDC210300D0201
Declaration of Conformity - CE:	9AKK1074920315
Instructions and Manuals:	1SDH001607R0001

External Classifications and Standards

ETIM 9:	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 10:	EC000228 - Power circuit-breaker for trafo/generator/installation protection
WEEE Category:	5. Small Equipment (No External Dimension More Than 50 cm)
eClass:	V11.1 : 27370409

Categories

Products > Low Voltage Products and Systems > Circuit Breakers > Moulded Case Circuit Breakers > Tmax T

© 2026 ABB. All rights reserved.



© 2026 ABB. All rights reserved.