National Semiconductor

February 1993

54AC/74AC157 • 54ACT/74ACT157
Quad 2-Input Multiplexer


General Description

The 'AC/'ACT157 is a high-speed quad 2-input multiplexer. Four bits of data from two sources can be selected using the common Select and Enable inputs. The four outputs present the selected data in the true (noninverted) form. The 'AC/'ACT157 can also be used as a function generator.

Features


- I_{CC} and I_{OZ} reduced by 50%
- Outputs source/sink 24 mA
- 'ACT157 has TTL-compatible inputs
- Standard Military Drawing (SMD)
  - — 'AC157: 5962-89539
  - — 'ACT157: 5962-89688

Logic Symbols



TL/F/9929–1

IEEE/IEC




TL/F/9929–2

Pin Names	Description
I_{0a}–I_{0d}	Source 0 Data Inputs
I_{1a}–I_{1d}	Source 1 Data Inputs
$\overline{E}$	Enable Input
S	Select Input
Z_a–Z_d	Outputs


Connection Diagrams

Pin Assignment for DIP, Flatpak and SOIC



TL/F/9929–3

Pin Assignment for LCC



TL/F/9929–4

FACT™ is a trademark of National Semiconductor Corporation.

©1995 National Semiconductor Corporation

RRD-B30M75/Printed in U. S. A.

Functional Description

The 'AC/'ACT157 is a quad 2-input multiplexer. It selects four bits of data from two sources under the control of a common Select input (S). The Enable input ($\overline{E}$) is active-LOW. When $\overline{E}$ is HIGH, all of the outputs (Z) are forced LOW regardless of all other inputs. The 'AC/'ACT157 is the logic implementation of a 4-pole, 2-position switch where the position of the switch is determined by the logic levels supplied to the Select input. The logic equations for the outputs are shown below:

$Z_a = \overline{E} \bullet (I_{1a} \bullet S + I_{0a} \bullet \overline{S})$
$Z_b = \overline{E} \bullet (I_{1b} \bullet S + I_{0b} \bullet \overline{S})$
$Z_c = \overline{E} \bullet (I_{1c} \bullet S + I_{0c} \bullet \overline{S})$
$Z_d = \overline{E} \bullet (I_{1d} \bullet S + I_{0d} \bullet \overline{S})$


A common use of the 'AC/ACT157 is the moving of data from two groups of registers to four common output busses. The particular register from which the data comes is determined by the state of the Select input. A less obvious use is as a function generator. The 'AC/'ACT157 can generate any four of the sixteen different functions of two variables with one variable common. This is useful for implementing gating functions.

Truth Table

Inputs				Outputs
$\overline{E}$	S	I_0	I_1	Z
H	X	X	X	L
L	H	X	L	L
L	H	X	H	H
L	L	L	X	L
L	L	H	X	H

H = HIGH Voltage Level
L = LOW Voltage Level
X = Immaterial

Logic Diagram



TL/F/9929–5

Please note that this diagram is provided only for the understanding of logic operations and should not be used to estimate propagation delays.

Absolute Maximum Rating (Note 1)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

Supply Voltage (V_{CC})	−0.5V to +7.0V
DC Input Diode Current (I_{IK})	
$V_I = -0.5V$	−20 mA
$V_I = V_{CC} + 0.5V$	+20 mA
DC Input Voltage (V_I)	−0.5V to V_{CC} + 0.5V
DC Output Diode Current (I_{OK})	
$V_O = -0.5V$	−20 mA
$V_O = V_{CC} + 0.5V$	+20 mA
DC Output Voltage (V_O)	−0.5V to V_{CC} + 0.5V
DC Output Source or Sink Current (I_O)	±50 mA
DC V_{CC} or Ground Current per Output Pin (I_{CC} or I_{GND})	±50 mA
Storage Temperature (T_{STG})	−65°C to +150°C
Junction Temperature (T_J)	
CDIP	175°C
PDIP	140°C

Note 1: Absolute maximum ratings are those values beyond which damage to the device may occur. The databook specifications should be met, without exception, to ensure that the system design is reliable over its power supply, temperature, and output/input loading variables. National does not recommend operation of FACT™ circuits outside databook specifications.

Recommended Operating Conditions

Supply Voltage (V_{CC})	
'AC	2.0V to 6.0V
'ACT	4.5V to 5.5V
Input Voltage (V_I)	0V to V_{CC}
Output Voltage (V_O)	0V to V_{CC}
Operating Temperature (T_A)	
74AC/ACT	−40°C to +85°C
54AC/ACT	−55°C to +125°C
Minimum Input Edge Rate ($\Delta V/\Delta t$) 'AC Devices V_{IN} from 30% to 70% of V_{CC} V_{CC} @ 3.3V, 4.5V, 5.5V	125 mV/ns
Minimum Input Edge Rate ($\Delta V/\Delta t$) 'ACT Devices V_{IN} from 0.8V to 2.0V V_{CC} @ 4.5V, 5.5V	125 mV/ns

DC Characteristics for 'AC Family Devices

Symbol	Parameter	V_{CC} (V)	74AC $T_A = +25°C$	74AC $T_A = -55°C$ to $+125°C$	54AC $T_A = -55°C$ to $+125°C$	74AC $T_A = -40°C$ to $+85°C$	Units	Conditions
			Typ	Guaranteed Limits				
V_{IH}	Minimum High Level Input Voltage	3.0	1.5	2.1	2.1	2.1	V	$V_{OUT} = 0.1V$ or $V_{CC} - 0.1V$
		4.5	2.25	3.15	3.15	3.15		
		5.5	2.75	3.85	3.85	3.85		
V_{IL}	Maximum Low Level Input Voltage	3.0	1.5	0.9	0.9	0.9	V	$V_{OUT} = 0.1V$ or $V_{CC} - 0.1V$
		4.5	2.25	1.35	1.35	1.35		
		5.5	2.75	1.65	1.65	1.65		
V_{OH}	Minimum High Level Output Voltage	3.0	2.99	2.9	2.9	2.9	V	$I_{OUT} = -50\ \mu A$
		4.5	4.49	4.4	4.4	4.4		
		5.5	5.49	5.4	5.4	5.4		
		3.0		2.56	2.4	2.46	V	*$V_{IN} = V_{IL}$ or V_{IH} I_{OH} −12 mA
		4.5		3.86	3.7	3.76		I_{OH} −24 mA
		5.5		4.86	4.7	4.76		−24 mA
V_{OL}	Maximum Low Level Output Voltage	3.0	0.002	0.1	0.1	0.1	V	$I_{OUT} = 50\ \mu A$
		4.5	0.001	0.1	0.1	0.1		
		5.5	0.001	0.1	0.1	0.1		
		3.0		0.36	0.50	0.44	V	*$V_{IN} = V_{IL}$ or V_{IH} I_{OL} 12 mA
		4.5		0.36	0.50	0.44		I_{OL} 24 mA
		5.5		0.36	0.50	0.44		24 mA
I_{IN}	Maximum Input Leakage Current	5.5		±0.1	±1.0	±1.0	μA	$V_I = V_{CC}$, GND

*All outputs loaded; thresholds on input associated with output under test.

DC Characteristics for 'AC Family Devices (Continued)

Symbol	Parameter	V_{CC} (V)	74AC $T_A = +25°C$	54AC $T_A = -55°C$ to $+125°C$	74AC $T_A = -40°C$ to $+85°C$	Units	Conditions
			Typ	Guaranteed Limits			
I_{OLD}	†Minimum Dynamic Output Current	5.5		50	75	mA	V_{OLD} = 1.65V Max
I_{OHD}		5.5		−50	−75	mA	V_{OHD} = 3.85V Min
I_{CC}	Maximum Quiescent Supply Current	5.5	4.0	80.0	40.0	μA	$V_{IN} = V_{CC}$ or GND

†Maximum test duration 2.0 ms, one output loaded at a time.

Note: I_{IN} and I_{CC} @ 3.0V are guaranteed to be less than or equal to the respective limit @ 5.5V V_{CC}. I_{CC} for 54AC @ 25°C is identical to 74AC @ 25°C.

DC Characteristics for 'ACT Family Devices

Symbol	Parameter	V_{CC} (V)	74ACT $T_A = +25°C$	54ACT $T_A = -55°C$ to $+125°C$	74ACT $T_A = -40°C$ to $+85°C$	Units	Conditions
			Typ	Guaranteed Limits			
V_{IH}	Minimum High Level Input Voltage	4.5 5.5	1.5 1.5	2.0 2.0	2.0 2.0	V	V_{OUT} = 0.1V or V_{CC} − 0.1V
V_{IL}	Maximum Low Level Input Voltage	4.5 5.5	1.5 1.5	0.8 0.8	0.8 0.8	V	V_{OUT} = 0.1V or V_{CC} − 0.1V
V_{OH}	Minimum High Level Output Voltage	4.5 5.5	4.49 5.49	4.4 5.4	4.4 5.4	V	I_{OUT} = −50 μA
		4.5 5.5		3.86 4.86	3.70 4.70	3.76 4.76	V	*V_{IN} = V_{IL} or V_{IH} I_{OH} −24 mA −24 mA
V_{OL}	Maximum Low Level Output Voltage	4.5 5.5	0.001 0.001	0.1 0.1	0.1 0.1	0.1 0.1	V	I_{OUT} = 50 μA
		4.5 5.5		0.36 0.36	0.50 0.50	0.44 0.44	V	*V_{IN} = V_{IL} or V_{IH} I_{OL} 24 mA 24 mA
I_{IN}	Maximum Input Leakage Current	5.5		±0.1	±1.0	±1.0	μA	$V_I = V_{CC}$, GND
I_{CCT}	Maximum I_{CC}/Input	5.5	0.6		1.6	1.5	mA	$V_I = V_{CC}$ − 2.1V
I_{OLD}	†Minimum Dynamic Output Current	5.5			50	75	mA	V_{OLD} = 1.65V Max
I_{OHD}		5.5			−50	−75	mA	V_{OHD} = 3.85V Min
I_{CC}	Maximum Quiescent Supply Current	5.5		4.0	80.0	40.0	μA	$V_{IN} = V_{CC}$ or GND

*All outputs loaded; thresholds on input associated with output under test.

†Maximum test duration 2.0 ms, one output loaded at a time.

Note: I_{CC} for 54ACT @ 25°C is identical to 74ACT @ 25°C.

AC Electrical Characteristics

Symbol	Parameter	V_{CC}* (V)	74AC $T_A = +25°C$, $C_L = 50$ pF			54AC $T_A = -55°C$ to $+125°C$, $C_L = 50$ pF		74AC $T_A = -40°C$ to $+85°C$, $C_L = 50$ pF		Units
			Min	Typ	Max	Min	Max	Min	Max	
t_{PLH}	Propagation Delay S to Z_n	3.3	1.5	7.0	11.5	1.0	16.0	1.5	13.0	ns
		5.0	1.5	5.5	9.0	1.0	12.0	1.5	10.0	
t_{PHL}	Propagation Delay S to Z_n	3.3	1.5	6.5	11.0	1.0	14.0	1.5	12.0	ns
		5.0	1.5	5.0	8.5	1.0	11.5	1.0	9.5	
t_{PLH}	Propagation Delay $\overline{E}$ to Z_n	3.3	1.5	7.0	11.5	1.0	16.0	1.5	13.0	ns
		5.0	1.5	5.5	9.0	1.0	12.0	1.5	10.0	
t_{PHL}	Propagation Delay $\overline{E}$ to Z_n	3.3	1.5	6.5	11.0	1.0	14.0	1.5	12.0	ns
		5.0	1.5	5.5	9.0	1.0	11.5	1.0	9.5	
t_{PLH}	Propagation Delay I_n to Z_n	3.3	1.5	5.0	8.5	1.0	11.0	1.0	9.0	ns
		5.0	1.5	4.0	6.5	1.0	9.0	1.0	7.0	
t_{PHL}	Propagation Delay I_n to Z_n	3.3	1.5	5.0	8.0	1.0	11.0	1.0	9.0	ns
		5.0	1.5	4.0	6.5	1.0	9.0	1.0	7.0	

*Voltage Range 3.3 is 3.3V ±0.3V
Voltage Range 5.0 is 5.0V ±0.5V

AC Electrical Characteristics

Symbol	Parameter	V_{CC}* (V)	74ACT $T_A = +25°C$, $C_L = 50$ pF			54ACT $T_A = -55°C$ to $+125°C$, $C_L = 50$ pF		74ACT $T_A = -40°C$ to $+85°C$, $C_L = 50$ pF		Units
			Min	Typ	Max	Min	Max	Min	Max	
t_{PLH}	Propagation Delay S to Z_n	5.0	2.0	5.5	9.0	1.0	11.5	1.5	10.0	ns
t_{PHL}	Propagation Delay S to Z_n	5.0	2.0	5.5	9.5	1.0	11.5	2.0	10.5	ns
t_{PLH}	Propagation Delay $\overline{E}$ to Z_n	5.0	1.5	6.0	10.0	1.0	12.0	1.5	11.5	ns
t_{PHL}	Propagation Delay $\overline{E}$ to Z_n	5.0	1.5	5.0	8.5	1.0	10.0	1.0	9.0	ns
t_{PLH}	Propagation Delay I_n to Z_n	5.0	1.5	4.0	7.0	1.0	8.5	1.0	8.5	ns
t_{PHL}	Propagation Delay I_n to Z_n	5.0	1.5	4.5	7.5	1.0	9.0	1.0	8.5	ns

*Voltage Range 5.0 is 5.0V ±0.5V

Capacitance

Symbol	Parameter	Typ	Units	Conditions
C_{IN}	Input Capacitance	4.5	pF	V_{CC} = OPEN
C_{PD}	Power Dissipation Capacitance	50.0	pF	V_{CC} = 5.0V

Ordering Information

The device number is used to form part of a simplified purchasing code where the package type and temperature range are defined as follows:

74ACT 157 P C QR

Temperature Range Family
- 74AC = Commercial
- 54AC = Military
- 74ACT = Commercial TTL-Compatible
- 54ACT = Military TTL-Compatible


Device Type

Package Code
- P = Plastic DIP
- D = Ceramic DIP
- F = Flatpak
- L = Leadless Ceramic Chip Carrier (LCC)
- S = Small Outline (SOIC)

Temperature Range
- C = Commercial (−40°C to +85°C)
- M = Military (−55°C to +125°C)

Special Variations
- X = Devices shipped in 13″ reels
- QR = Commercial grade device with burn-in
- QB = Military grade device with environmental and burn-in processing shipped in tubes


Physical Dimensions inches (millimeters)




E20A (REV D)


20 Terminal Ceramic Leadless Chip Carrier (L)
NS Package Number E20A

Physical Dimensions inches (millimeters) (Continued)




16-Lead Ceramic Dual-In-Line Package (D)
NS Package Number J16A






16-Lead Small Outline Integrated Circuit (S)
NS Package Number M16A

Physical Dimensions inches (millimeters) (Continued)



16-Lead Plastic Dual-In-Line Package (P)
NS Package Number N16E



16-Lead Ceramic Flatpak (F)
NS Package Number W16A

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

National Semiconductor Corporation
2900 Semiconductor Drive
P.O. Box 58090
Santa Clara, CA 95052-8090
Tel: 1(800) 272-9959
TWX: (910) 339-9240

National Semiconductor GmbH
Livry-Gargan-Str. 10
D-82256 Fürstenfeldbruck
Germany
Tel: (81-41) 35-0
Telex: 527649
Fax: (81-41) 35-1

National Semiconductor Japan Ltd.
Sumitomo Chemical
Engineering Center
Bldg. 7F
1-7-1, Nakase, Mihama-Ku
Chiba-City,
Ciba Prefecture 261
Tel: (043) 299-2300
Fax: (043) 299-2500

National Semiconductor Hong Kong Ltd.
13th Floor, Straight Block,
Ocean Centre, 5 Canton Rd.
Tsimshatsui, Kowloon
Hong Kong
Tel: (852) 2737-1600
Fax: (852) 2736-9960

National Semiconductores Do Brazil Ltda.
Rue Deputado Lacorda Franco
120-3A
Sao Paulo-SP
Brazil 05418-000
Tel: (55-11) 212-5066
Telex: 391-1131931 NSBR BR
Fax: (55-11) 212-1181

National Semiconductor (Australia) Pty, Ltd.
Building 16
Business Park Drive
Monash Business Park
Nottinghill, Melbourne
Victoria 3168 Australia
Tel: (3) 558-9999
Fax: (3) 558-9998

National does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and National reserves the right at any time without notice to change said circuitry and specifications.